


## Cuscinetti a rullini GBR243320-U-IKO - GBR243320-U-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/rullini/gbr243320-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)		
	With two seals	With 6/16 seal		$F_w$	$D$	$C$
<b>38.100</b> (1.5)	<b>GBR 243320 UU</b>		200	38.100(1.5)	52.388(2.06)	31.750(1.25)
Standard mounting dimensions mm		Ball dynamic load rating $C$	Ball static load rating $C_0$	Allowable rotational speed <sup>(*)</sup>		
$D_s$ Max.	$r$ as max ( <sup>(†)</sup> )	N	N	rpm		
47.3	0.6	54 200	97 700	2 000		

Notes: (\*) Minimum allowable value of chamfer dimension  $r$   
(†) Allowable rotational speed applies to grease lubrication.  
Remark: The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

## CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952382982
Diametro interno	38.1 mm
Diametro esterno	52.388 mm
Spessore	31.75 mm
Imballaggio	1

[contatto@123cuscinetti.it](mailto:contatto@123cuscinetti.it)

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE