


Cuscinetti a rullini GBR324120-UU-IKO - GBR324120-UU-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/rullini/gbr324120-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)		
	With two seals	With one seal		F_w	D	C
50.800 (2)	GBR 324120 UU		255	50.800 \pm 0.01	65.088 \pm 0.01	31.750 \pm 0.01
Standard mounting dimensions mm		Seal dynamic load rating C	Ball static load rating C_0	Allowable rotational speed ^(*)		
D_A	r as max	N	N	rpm		
Max.	1	63 100	130 000	1 600		

Notes: (*) Minimum allowable value of diameter dimension r
(**) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952383071
Diametro interno	50.8 mm
Diametro esterno	65.088 mm
Spessore	31.75 mm
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE