


## Cuscinetti a rullini GBR405228-UU-IKO - GBR405228-UU-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/rullini/gbr405228-uu-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)		
	With two seals	With one seal		$F_w$	$D$	$C$
<b>63.500</b> (2 1/2)	<b>GBR 405228 UU</b>		560	63.500 (2 1/2)	82.550 (3 1/4)	44.450 (1 3/4)
Standard mounting dimensions mm		Seal dynamic load rating $C$	Ball static load rating $C_0$	Allowable rotational speed <sup>(*)</sup>		
$D_A$ Max.	$r$ as max ( <sup>(†)</sup> )	N	N	rpm		
75.7	1.5	93 300	179 000	1 300		

Notes: (\*) Minimum allowable value of diameter dimension  $r$   
(†) Allowable rotational speed applies to grease lubrication.  
Remark: This roller ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

## CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952383125
Diametro interno	63.5 mm
Diametro esterno	82.55 mm
Spessore	44.45 mm
Imballaggio	1

[contatto@123cuscinetti.it](mailto:contatto@123cuscinetti.it)

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE