


Cuscinetti a rullini GBR648032-U-IKO - GBR648032-U-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/rullini/gbr648032-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)		
	With two seals	With one seal		F_w	D	C
101.600 (4)	GBR 648032 U		1 380	101.600 (4)	127.000 (5)	50.800 (2)
Standard mounting dimensions mm		Seal dynamic load rating C	Ball diameter d_b	Allowable rotational speed ^(*)		
D_A	r as max	N	N	rpm		
119	1.5	182 000	395 000	800		

Notes: (*) Minimum allowable value of diameter dimension r
(**) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952383231
Diametro interno	101.6 mm
Diametro esterno	127 mm
Spessore	50.8 mm
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE