


Cuscinetti a rullini GBRI406028-UU-IKO - GBRI406028-UU-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/rullini/gbri406028-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)					
	With two seals	With one seal		d	D	C			
63.500 (2 1/2)	GBRI 406028 UU		1 140	63.500 ± 0.02	95.250 ± 0.02	44.450 ± 0.02			
B	F _w	Standoff mounting dimensions - mm		Basic dynamic load rating C N	Basic static load rating C ₀ N	Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring		
		Min.	Max.					D _s Max.	r _{as max} ⁽¹⁾
44.700	76.200 ± 0.03	71	73	88	1.5	101 000	215 000	1 100	LRBZ 404828

Notes: (1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to grease lubrication.
Remark: This outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952383569
Diametro interno	63.5 mm
Diametro esterno	95.25 mm
Spessore	44.45 mm
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE