

Cuscinetti a rullini RNAFW162420-IKO - RNAFW162420-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/rullini/rnafw162420-iko>

IKO
NEEDLE ROLLER BEARINGS WITH SEPARABLE CAGE
Without inner Ring

| Shaft dia. mm | Identification number | Mass (Ref.) g | Boundary dimensions mm | | | | Standard mounting dimensions mm | | | Basic dynamic load rating C N | Basic static load rating C ₀ N |
|------------------|-----------------------|---------------------|------------------------|----|----|--|---------------------------------|------------------------|----------------|-------------------------------------|---|
| | | | F _w | D | C | r ⁽¹⁾ r _{s min} | d _b | D _s Max. | D _b | | |
| 16 | RNAFW 162420 | 32 | 16 | 24 | 20 | 0.3 | 19.6 | 22 | 16.6 | 11 900 | 16 700 |

Allowable rotational speed⁽²⁾
rpm
30 000

Notes⁽¹⁾ Minimum allowable value of chamfer dimension r.
⁽²⁾ Allowable rotational speed applies to grease lubrication.
Remark: This roller ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARATTERISTICHE DEL PRODOTTO

| | |
|------------------|---------------|
| Marchio | IKO |
| N° Ean13 | 3663952383798 |
| Diametro interno | 16 mm |
| Diametro interno | 0.63" inch |
| Diametro esterno | 24 mm |
| Diametro esterno | 0.945" inch |
| Spessore | 20 mm |
| Spessore | 0.787" inch |
| Imballaggio | 1 |

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE