


Cuscinetti a rullini TRU405930-IKO - TRU405930-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/rullini/tru405930-iko>

IKO

ROLLER BEARINGS

Caged Roller Bearings
Full Complement Roller Bearings



NAU49 TRU

Shaft dia. mm	Identification number		Mass (Ref.) g	Boundary dimensions mm					
	Full complement type	Caged type		d	D	C	r ⁽¹⁾ F _s min	J	E _w
40	—	TRU 405930	265	40	59	30	0.6	45	52.5
Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽²⁾							
N	N	rpm							
34 700	62 500	8 500							

Notes: (1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to grease lubrication.
Remark: This roller ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952385365
Diametro interno	40 mm
Diametro esterno	59 mm
Spessore	30 mm
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE