


## Cuscinetti a rullini NAU4916-IKO - NAU4916-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/rullini/nau4916-iko>

**IKO**  
**ROLLER BEARINGS**  
Caged Roller Bearings  
Full Complement Roller Bearings



NAU49 TRU

Shaft dia. mm	Identification number		Mass (Ref.) g	Boundary dimensions mm					
	Full complement type	Caged type		d	D	C	r <sup>(1)</sup> F <sub>s</sub> min	J	E <sub>w</sub>
80	—	NAU 4916	790	80	110	30	1	89.5	102
Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed <sup>(2)</sup>							
N	N	rpm							
57 200	95 500	4 500							

Notes: (1) Minimum allowable value of chamfer dimension r  
(2) Allowable rotational speed applies to grease lubrication.  
Remark: This roller ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

## CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952385587
Diametro interno	80 mm
Diametro esterno	110 mm
Spessore	30 mm
Imballaggio	1

[contatto@123cuscinetti.it](mailto:contatto@123cuscinetti.it)

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE