


Cuscinetti a rullini
NAU4905-UU-IKO - NAU4905-UU-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/rullini/nau4905-uu-iko>



ROLLER BEARINGS

Caged Roller Bearings **With Seal**
Full Complement Roller Bearings **With Seal**



NAU49-UU
TRU-UU

Shaft dia. mm	Identification number			Mass (Ref.) g	Boundary dimensions mm				
	Full complement type	Caged type			d	D	C	r _{1 min}	J
25	---	NAU 4905UU		89	25	42	17	0.3	29.5
	Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed n _{rm}						
E _w	N	N							
37	11 900	13 900	6 500						

Notes: (1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.
Remarks: 1. The NAU and TRU series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.
2. The bearings with seals are provided with prepacked grease.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952385938
Diametro interno	25 mm
Diametro esterno	42 mm
Spessore	17 mm
Imballaggio	1

contatto@123cuscinetti.it
+33 3 59 36 04 90
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE