


Cuscinetti a rullini
NAU4907-UU-IKO - NAU4907-UU-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/rullini/nau4907-uu-iko>


ROLLER BEARINGS
Caged Roller Bearings 
Full Complement Roller Bearings 


NAU49-UU
TRU-UU

Shaft dia. mm	Identification number		Mass (Ref.) g	Boundary dimensions mm				
	Full complement type	Caged type		d	D	C	r ₁ min	J
35	---	NAU 4907UU	168	35	55	20	0.6	40
	Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed rpm					
49	19 500	26 300	4 500					

Notes: (1) Minimum allowable value of chamfer dimension r

(2) Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.

Remarks: 1. The NAU and TRU series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.

2. The bearings with seals are provided with prepacked grease.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952385990
Diametro interno	35 mm
Diametro esterno	55 mm
Spessore	20 mm
Imballaggio	1

contatto@123cuscinetti.it
+33 3 59 36 04 90
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE