


Cuscinetti a rullini TRU456430-UU-IKO - TRU456430-UU-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/rullini/tru456430-uu-iko>

IKO
ROLLER BEARINGS
Caged Roller Bearings **[With Seal]**
Full Complement Roller Bearings **[With Seal]**



Shaft dis. mm	Identification number			Mass (Ref.) g	Boundary dimensions mm				
	Full complement type	Caged type			d	D	C	r _{ext} ⁽¹⁾	J
45	---	---	TRU 456430UU	295	45	64	30	0.6	50.5
<i>E_w</i>	Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed n ₂ rpm						
61	36 400	54 700	2 500						

Notes^(*) Minimum allowable value of chamfer dimension r
⁽¹⁾ Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.
 Remarks: 1. The NAU and NAG series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.
 2. The bearings with seals are provided with prepacked grease.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952386171
Diametro interno	45 mm
Diametro interno	1.772" inch
Diametro esterno	64 mm
Diametro esterno	2.52" inch
Spessore	30 mm
Spessore	1.181" inch
Peso	300 g
Imballaggio	1
Standard	Nessuno standard

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE