


Cuscinetti a rullini NAU4912-UU-IKO - NAU4912-UU-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/rullini/nau4912-uu-iko>

IKO
ROLLER BEARINGS
Caged Roller Bearings **[With Seal]**
Full Complement Roller Bearings **[With Seal]**



Shaft dis. mm	Identification number		Mass (Ref.) g	Boundary dimensions mm				
	Full complement type	Caged type		d	D	C	r _{min} ⁽¹⁾	J
60	—	NAU 4912UU	415	60	85	25	1	67
E_w	Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed n _{gr}					
77.5	34 700	51 400	3,000					

Notes: ⁽¹⁾ Minimum allowable value of chamfer dimension r.
⁽²⁾ Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.
Remarks: 1. The NAU and NAU series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.
2. The bearings with seals are provided with prepacked grease.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952386263
Diametro interno	60 mm
Diametro interno	2.362" inch
Diametro esterno	85 mm
Diametro esterno	3.346" inch
Spessore	25 mm
Spessore	0.984" inch
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE