



## Cuscinetti a rullini NAS5013-ZZ-NR-IKO - NAS5013-ZZ-NR-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/rullini/nas5013-zz-nr-iko>

IKO  
**ROLLER BEARINGS**  
Roller Bearings for Sheaves

NAS50-ZZNR

Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						
	Sealed type	Shield type		d	D	D <sub>2</sub>	B	C	C <sub>1</sub>	S
65		NAS 5013ZZNR	1.30	65	100	104.8	46	45	34	5.5
<i>f</i>	<i>c</i>	<i>r</i> mm <sup>(1)</sup>	<i>J</i>	Basic dynamic load rating C N		Static load rating C <sub>0</sub> N		Allowable rotational speed <sup>(2)</sup> rpm		
2.5	2	0.6	78	128 000		224 000		1 600		

Notes: <sup>(1)</sup> Minimum allowable value of chamfer dimension *r*.  
<sup>(2)</sup> Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.  
Remarks: 1. The NAS and NAU series with a bore diameter, *d*, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.  
2. The bearings with seals are provided with prepacked grease.

### CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952386836
Diametro interno	65 mm
Diametro interno	2.559" inch
Diametro esterno	100 mm
Diametro esterno	3.937" inch
Spessore	46 mm
Spessore	1.811" inch
Imballaggio	1

[contatto@123cuscinetti.it](mailto:contatto@123cuscinetti.it)

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE