


## Cuscinetti a rullini NAS5017-ZZ-NR-IKO - NAS5017-ZZ-NR-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/rullini/nas5017-zz-nr-iko>

IKO  
**ROLLER BEARINGS**  
Roller Bearings for Sheaves



Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						
	Sealed type	Shield type		d	D	D <sub>2</sub>	B	C	C <sub>1</sub>	S
85		NAS 5017ZZNR	2.80	85	130	134.5	60	59	48	5.5
<i>f</i>	<i>c</i>	<i>r</i> mm <sup>(1)</sup>	<i>J</i>	Basic dynamic load rating C <sub>r</sub> N	Static load rating C <sub>0</sub> N	Allowable rotational speed <sup>(2)</sup> rpm				
2.5	2	0.6	101	257 000	446 000	1 200				

Notes<sup>(1)</sup> Minimum allowable value of chamfer dimension *r*  
<sup>(2)</sup> Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.  
 Remarks: 1. The NAG and NAU series with a bore diameter, *d*, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.  
 2. The bearings with seals are provided with prepacked grease.

## CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952386911
Diametro interno	85 mm
Diametro esterno	130 mm
Spessore	60 mm
Imballaggio	1

[contatto@123cuscinetti.it](mailto:contatto@123cuscinetti.it)

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE