



Cuscinetti a rullini NAS5060-UU-IKO - NAS5060-UU-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/rullini/nas5060-uu-iko>

IKO
ROLLER BEARINGS
Roller Bearings for Sheaves

NAS50-UUNR

| Shaft dia. mm | Identification number | | Mass (Ref.) kg | Boundary dimensions mm | | | | | | |
|---------------|-----------------------|-------------|----------------|------------------------|-----|----------------|-----|-----|----------------|---|
| | Sealed type | Shield type | | d | D | D ₂ | B | C | C ₁ | S |
| 300 | NAS 5060UU | | 130 | 300 | 460 | — | 218 | 216 | — | — |

| f | c | r _s mm ⁽¹⁾ | J | Basic dynamic load rating C N | Static load rating C ₀ N | Allowable rotational speed ⁽²⁾ rpm |
|---|---|----------------------------------|-----|-------------------------------|-------------------------------------|---|
| — | 5 | 2 | 359 | 2 670 000 | 5 870 000 | 300 |

Notes⁽¹⁾ Minimum allowable value of chamfer dimension r
⁽²⁾ Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.
 Remarks: 1. The NAS and NAU series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.
 2. The bearings with seals are provided with prepacked grease.

CARATTERISTICHE DEL PRODOTTO

| | |
|------------------|---------------|
| Marchio | IKO |
| N° Ean13 | 3663952387277 |
| Diametro interno | 300 mm |
| Diametro esterno | 460 mm |
| Spessore | 218 mm |
| Imballaggio | 1 |

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE