



## Cuscinetti a rullini NAS5068-UU-IKO - NAS5068-UU-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/rullini/nas5068-uu-iko>

IKO  
**ROLLER BEARINGS**  
Roller Bearings for Sheaves

NAS50-UUNR

Shaft dia. mm	Identification number			Mass (Ref.) kg	Boundary dimensions mm						
	Sealed type	Shield type			d	D	D <sub>2</sub>	B	C	C <sub>1</sub>	S
340	NAS 5068UU			180	340	520	—	243	241	—	—

f	c	r <sub>s</sub> mm <sup>(1)</sup>	J	Basic dynamic load rating C N	Static load rating C <sub>0</sub> N	Allowable rotational speed <sup>(2)</sup> rpm
—	6	2.5	404	3 370 000	7 560 000	300

Notes<sup>(1)</sup> Minimum allowable value of chamfer dimension r  
<sup>(2)</sup> Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.  
 Remarks: 1. The NAS and NAU series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.  
 2. The bearings with seals are provided with prepacked grease.

## CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952387314
Diametro interno	340 mm
Diametro esterno	520 mm
Spessore	243 mm
Imballaggio	1

[contatto@123cuscinetti.it](mailto:contatto@123cuscinetti.it)

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE