


## Cuscinetti a rullini NAS5084-ZZ-IKO - NAS5084-ZZ-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/rullini/nas5084-zz-iko>

IKO  
**ROLLER BEARINGS**  
Roller Bearings for Sheaves



NAS50-ZZNR

Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm							
	Sealed type	Shield type		d	D	D <sub>2</sub>	B	C	C <sub>1</sub>	S	
420		NAS 5084ZZ	275	420	620	—	272	270	—	—	
	f	c	r <sub>s</sub> mm <sup>(1)</sup>	J	Basic dynamic load rating C N	Static load rating C <sub>0</sub> N	Allowable rotational speed <sup>(2)</sup> rpm				
	—	6	2.5	490	4 390 000	10 400 000	250				

Notes<sup>(1)</sup> Minimum allowable value of chamfer dimension r.  
<sup>(2)</sup> Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.  
Remarks: 1. The NAS and NAU series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.  
2. The bearings with seals are provided with prepacked grease.

## CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952387406
Diametro interno	420 mm
Diametro esterno	620 mm
Spessore	272 mm
Imballaggio	1

[contatto@123cuscinetti.it](mailto:contatto@123cuscinetti.it)

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE