

Cuscinetti a rullini NBX6040Z-IKO - NBX6040Z-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/rullini/nbx6040z-iko>

IKO

COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing Without Inner Ring
Needle Roller Bearings with Thrust Roller Bearing Without Inner Ring

Identification number												
Shaft dia. mm	Mass (Ref.) g		With dust cover	Mass (Ref.) g		Mass (Ref.) g		With dust cover	Mass (Ref.) g			
60	---		---	---		---		---	NBX 6040Z 538			
Boundary dimensions mm												
F_w	D	D_1	D_2	L	H	r_1 min.	d_1	Basic load rating C	Basic static load rating C_0	Allowable rotational speed ⁽²⁾ rpm		
60	72	85	86.5	40	17	1	60	47 500	64 600	103 000	224 000	4 000

Notes:
(1) Minimum allowable value of chamfer dimension r .
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NBX series.

Remarks:
1. The outer ring has an oil groove and an oil hole.
2. Grease is not prepacked. Perform proper lubrication.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952390529
Diametro interno	60 mm
Diametro esterno	72 mm
Spessore	40 mm
Imballaggio	1
Standard	Nessuno standard

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE