

## Cuscinetti a rullini NAX7040Z-IKO - NAX7040Z-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/rullini/nax7040z-iko>

**IKO**  
**COMBINED TYPE NEEDLE ROLLER BEARINGS**  
Needle Roller Bearings with Thrust Ball Bearing Without Inner Ring  
Needle Roller Bearings with Thrust Roller Bearing Without Inner Ring

Identification number														
Shaft dia. mm	Mass (Ref.) g		With dust cover		Mass (Ref.) g		With dust cover		Mass (Ref.) g					
	70	NAX 7040Z		606		—		—		—				
Boundary dimensions mm														
$F_w$	$D$	$D_1$	$D_2$	$L$	$H$	$r_1$ min.	$d_f$	Basic load rating $C$	Basic static load rating $C_0$	Allowable rotational speed <sup>(2)</sup> rpm				
70	85	95	96.5	40	18	11	1	70	85	55 500	43 100	120 000	101 000	3 500

Notes:  
(1) Minimum allowable value of chamfer dimension  $r$ .  
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.

Remarks:  
1. The outer ring has an oil groove and an oil hole.  
2. Grease is not prepacked. Perform proper lubrication.

## CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952390550
Diametro interno	70 mm
Diametro interno	2.756" inch
Diametro esterno	85 mm
Diametro esterno	3.346" inch
Spessore	40 mm
Spessore	1.575" inch
Imballaggio	1

[contatto@123cuscinetti.it](mailto:contatto@123cuscinetti.it)

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE