

Cuscinetti a rullini NAX7040Z-IKO - NAX7040Z-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/rullini/nax7040z-iko>

IKO

COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing Without Inner Ring
Needle Roller Bearings with Thrust Roller Bearing Without Inner Ring

Identification number										
Shaft dia. mm	Mass (Ref.) g		With dust cover		Mass (Ref.) g		With dust cover		Mass (Ref.) g	
	NAX 7040Z		606		—		—			
70	—		—		—		—		—	
Boundary dimensions mm										
F_w	D	D_1	D_2	L	H	r_1 min.	d_f	Basic load ratings C	Basic static load rating C_0	Allowable rotational speed ⁽²⁾ rpm
70	85	95	96.5	40	18	1	70	55 500	43 100	120 000
								Radial	Radial	Radial
								N	N	N
								Radial	Radial	Radial
								N	N	N
								Axial	Axial	Axial
								N	N	N
								Axial	Axial	Axial
								N	N	N
								rpm	rpm	rpm
								3 500	3 500	3 500

Notes:
(1) Minimum allowable value of chamfer dimension r .
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.

Remarks:
1. The outer ring has an oil groove and an oil hole.
2. Grease is not prepacked. Perform proper lubrication.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952390550
Diametro interno	70 mm
Diametro esterno	85 mm
Spessore	40 mm
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE