

Cuscinetti a rullini NAXI1223-IKO - NAXI1223-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/rullini/naxi1223-iko>

IKO
COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**

Identification number									
Shaft dia. mm	Mass (Ref.) g	With dust cover	Mass (Ref.) g	Mass (Ref.) g	With dust cover	Mass (Ref.) g	d	D	D ₁
12	NAXI 1223	55.5	—	—	—	—	12	24	28
Boundary dimensions mm									
D ₂	L	B	H	I ₁	r ⁽¹⁾	r ⁽²⁾	d ₄	d ₅	Assembled inner ring
25	23	16	9	6.5	0.3	0.2	10	18	LRT 71016
Basic dynamic load rating C									
Basic static load rating C ₀									
Allowable rotational speed ⁽³⁾									
		Radial		Axial		Radial		Axial	
		N		N		N		N	
		rpm		rpm		rpm		rpm	

Notes:
(1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.
Remarks:
1. The outer ring has an oil groove and an oil hole.
2. Grease is not prepacked. Perform proper lubrication.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952390680
Diametro interno	12 mm
Diametro esterno	24 mm
Spessore	23 mm
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE