

Cuscinetti a rullini NBXI1223Z-IKO - NBXI1223Z-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/rullini/nbxi1223z-iko>

UNIDIRECTIONAL TYPE NEEDLE ROLLER BEARINGS

Needle Bearings with Thrust Ball Bearing **With Inner Ring**
Needle Bearings with Thrust Roller Bearing **With Inner Ring**

Identification number														
Mass (Ref.) g		With dust cover		Mass (Ref.) g		Mass (Ref.) g		With dust cover		Mass (Ref.) g		d		
---		---		---		NBXI 1223Z		63		12		12		
Boundary dimensions mm			Number of rollers	Bore diameter mm		Basic dynamic load rating C		Basic static load rating C ₀		Allowable rotational speed ¹⁾ rpm	Assemble			
B	H	I_1		d_{min}	d_{max}	Radial	Axial	Radial	Axial					
16.5	9	6.5	0.3	0.3	15	15	26	14	12 300	10 200	14 900	23 900	14 000	LRT 1

1) Minimum allowable value of chamfer dimension r.
Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in IAX series, and a maximum of 25% of this value is allowable in the NBXI series.
The outer ring has an oil groove and an oil hole.
Grease is not prepacked. Perform proper lubrication.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952390710
Diametro interno	12 mm
Diametro esterno	24 mm
Spessore	23 mm
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE