

## Cuscinetti a rullini NBXI1730-IKO - NBXI1730-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/rullini/nbxi1730-iko>

**IKO**  
**COMBINED TYPE NEEDLE ROLLER BEARINGS**

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**  
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**

Identification number												
Shaft dia. mm	Mass (Ref.) g	With dust cover	Mass (Ref.) g	Mass (Ref.) g	With dust cover	Mass (Ref.) g	d	D	D <sub>1</sub>			
17	---	---	---	<b>NBXI 1730</b>	108	---	17	30	35			
Boundary dimensions mm												
D <sub>2</sub>	L	B	H	I <sub>1</sub>	r <sup>(1)</sup>	r <sup>(2)</sup>	d <sub>4</sub>	d <sub>5</sub>	Assembled inner ring			
36	30	20.5	10	10.5	0.3	0.3	20	33	19			
Basic dynamic load rating C												
Basic static load rating C <sub>0</sub>												
Allowable rotational speed <sup>(3)</sup>												
							17 600	19 000	25 400	48 700	11 000	LRT 172020

Notes:  
(1) Minimum allowable value of chamfer dimension r.  
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.  
Remarks:  
1. The outer ring has an oil groove and an oil hole.  
2. Grease is not prepacked. Perform proper lubrication.

## CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952390789
Diametro interno	17 mm
Diametro esterno	30 mm
Spessore	30 mm
Imballaggio	1

[contatto@123cuscinetti.it](mailto:contatto@123cuscinetti.it)

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE