

Cuscinetti a rullini NBXI2030Z-IKO - NBXI2030Z-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/rullini/nbxi2030z-iko>

IKO
COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**

Identification number																
Shaft dia. mm	Mass (Ref.) g			Mass (Ref.) g			Mass (Ref.) g			d	D	D ₁				
	---	---	---	---	---	---	---	---	---							
20	---	---	---	NBXI 2030Z			175	20	37	42						
Boundary dimensions mm																
D ₂	L	B	H	I ₁	r _{max}	r _{min}	d ₁	d ₂	d ₃	Radial	Axial	Radial	Axial	Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring	
43	30	20.5	11	9.5	0.6	0.3	25	25	40	24	20 000	22 700	32 100	60 700	9 000	LRT 202520

Notes⁽¹⁾ Minimum allowable value of chamfer dimension r.
⁽²⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NBX series.
Remarks: Z: The outer ring has an oil groove and an oil hole.
2: Grease is not prepacked. Perform proper lubrication.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952390833
Diametro interno	20 mm
Diametro esterno	37 mm
Spessore	30 mm
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE