

## Cuscinetti a rullini NAXI2530-IKO - NAXI2530-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/rullini/naxi2530-iko>

**IKO**  
**COMBINED TYPE NEEDLE ROLLER BEARINGS**

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**  
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**

Shaft dia. mm	Identification number								
	Mass (Ref.) g	With dust cover	Mass (Ref.) g	Mass (Ref.) g	With dust cover	Mass (Ref.) g	d	D	D <sub>1</sub>
25	NAXI 2530	179	—	—	—	—	25	42	47

Boundary dimensions mm				Basic dynamic load rating C	Basic static load rating C <sub>0</sub>		Allowable rotational speed <sup>(2)</sup> rpm	Assembled inner ring	
D <sub>2</sub>	L	B	H		Radial	Axial			
48	30	20.5	11	25 100	20 400	40 100	33 600	6 500	LRT 253020

Notes<sup>(1)</sup> Minimum allowable value of chamfer dimension r.  
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.  
Remarks: 1. The outer ring has an oil groove and an oil hole.  
2. Grease is not prepacked. Perform proper lubrication.

### CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952390840
Diametro interno	25 mm
Diametro interno	0.984" inch
Diametro esterno	42 mm
Diametro esterno	1.654" inch
Spessore	30 mm
Spessore	1.181" inch
Imballaggio	1

[contatto@123cuscinetti.it](mailto:contatto@123cuscinetti.it)

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE