

Cuscinetti a rullini NAXI3030Z-IKO - NAXI3030Z-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/rullini/naxi3030z-iko>

IKO
COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**

| Identification number | | | | | | | | | |
|-----------------------|---------------|-------------------|---------------|---------------|-----------------|---------------|----|----|----------------|
| Shaft dia. mm | Mass (Ref.) g | With dust cover | Mass (Ref.) g | Mass (Ref.) g | With dust cover | Mass (Ref.) g | d | D | D ₁ |
| 30 | | NAXI 3030Z | 215 | --- | --- | --- | 30 | 47 | 52 |

| Boundary dimensions mm | | | | | | | | | | Basic dynamic load rating C | Basic static load rating C ₀ | | Allowable rotational speed ⁽¹⁾ rpm | Assembled inner ring | | |
|------------------------|----|----|----|----------------|------------------|------------------|----------------|----------------|------|-----------------------------|---|--------|---|----------------------|--------|------------|
| D ₂ | L | B | H | I ₁ | r _{max} | r _{min} | d ₄ | d ₅ | Min. | | Radial | Axial | | | Radial | Axial |
| 53 | 30 | 20 | 12 | 9 | 0.6 | 0.3 | 35 | 35 | 45 | 34 | 26 900 | 21 200 | 46 200 | 37 600 | 6 000 | LRT 303520 |

Notes⁽¹⁾ Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. Grease is not prepacked. Perform proper lubrication.

CARATTERISTICHE DEL PRODOTTO

| | |
|------------------|---------------|
| Marchio | IKO |
| N° Ean13 | 3663952390888 |
| Diametro interno | 30 mm |
| Diametro esterno | 47 mm |
| Spessore | 30 mm |
| Imballaggio | 1 |

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE