

Cuscinetti a rullini NAXI3532-IKO - NAXI3532-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/rullini/naxi3532-iko>

IKO
COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**

Identification number											
Shaft dia. mm	Mass (Ref.) g		With dust cover		Mass (Ref.) g		With dust cover		d	D	D ₁
	35	NAXI 3532	265	—	—	—	—	—			
Boundary dimensions mm											
D ₂	L	B	H	I ₁	r ⁽¹⁾	r ⁽²⁾	d ₄	d ₅	d	Assembled inner ring	
61	32	20	13	10	0.6	0.3	40	40	52	39	LRT 354020
Basic dynamic load rating C											
Basic static load rating C ₀											
Allowable rotational speed ⁽³⁾											
Remarks											

Notes⁽¹⁾ Minimum allowable value of chamfer dimension r.
⁽²⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.
 Remark 1. The outer ring has an oil groove and an oil hole.
 2. Grease is not prepacked. Perform proper lubrication.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952390925
Diametro interno	35 mm
Diametro esterno	52 mm
Spessore	32 mm
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE