

Cuscinetti a rullini NAXI4032-IKO - NAXI4032-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/rullini/naxi4032-iko>

IKO
COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**

Identification number															
Shaft dia. mm	Mass (Ref.) g		With dust cover	Mass (Ref.) g		Mass (Ref.) g		With dust cover		Mass (Ref.) g		d	D	D ₁	
	40	NAXI 4032	315	---	---	---	---	---	---	---	---				40
Boundary dimensions mm			r ⁽¹⁾	r _{max}	r _{min}	d ₄	d ₅	Basic dynamic load rating C		Basic static load rating C ₀		Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring LRT 404520		
D ₂	L	B						H	I ₁	Radial	Axial			Radial	Axial
66.5	32	20	14	9	0.6	0.3	45	57	44	31 000	27 900	60 200	55 100	5 000	LRT 404520

Notes:
(1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.
Remarks:
1. The outer ring has an oil groove and an oil hole.
2. Grease is not prepacked. Perform proper lubrication.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952390963
Diametro interno	40 mm
Diametro esterno	58 mm
Spessore	32 mm
Imballaggio	-

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE