

Cuscinetti a rullini NAXI4535Z-IKO - NAXI4535Z-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/rullini/naxi4535z-iko>

IKO
COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**

| Shaft dia. mm | Identification number | | | | | | d | D | D ₁ |
|------------------|-----------------------|-----------------|------------------|-----------------|------------------|-----------------|----|----|----------------|
| | Mass (Ref.) g | With dust cover | Mass (Ref.) g | With dust cover | Mass (Ref.) g | With dust cover | | | |
| 45 | NAXI 4535Z 368 | | | | | | 45 | 62 | 70 |

| Boundary dimensions mm | | | | Bore chamfer mm | Basic dynamic load rating C | Basic static load rating C ₀ | | Allowable rotational speed ⁽²⁾ rpm | Assembled inner ring | | | | | | | |
|---------------------------|----|----|----|--------------------|--------------------------------|--|--------|--|----------------------|-------|-----|----|-----|---|-----|------------|
| D ₂ | L | B | H | | | Radial | Radial | | | Axial | | | | | | |
| 71.5 | 35 | 25 | 14 | 10 | 49 | 42 | 200 | 28 | 800 | 83 | 400 | 60 | 100 | 4 | 500 | LRT 455025 |

Notes:
(1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.
Remarks:
Z: The outer ring has an oil groove and an oil hole.
2: Grease is not prepacked. Perform proper lubrication.

CARATTERISTICHE DEL PRODOTTO

| | |
|------------------|---------------|
| Marchio | IKO |
| N° Ean13 | 3663952391014 |
| Diametro interno | 45 mm |
| Diametro esterno | 62 mm |
| Spessore | 35 mm |
| Imballaggio | 1 |

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE