

## Cuscinetti a rullini NBXI4535-IKO - NBXI4535-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/rullini/nbxi4535-iko>

**IICO**  
**COMBINED TYPE NEEDLE ROLLER BEARINGS**

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**  
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**

Shaft dia. mm	Identification number						d	D	D <sub>i</sub>
	Mass (Ref.) g	With dust cover	Mass (Ref.) g	Mass (Ref.) g	With dust cover	Mass (Ref.) g			
45	---	---	---	<b>NBXI 4535</b>	366	---	45	62	70

Boundary dimensions mm			Lead-in chamfer mm	Basic dynamic load rating C	Basic static load rating C <sub>0</sub>		Allowable rotational speed <sup>(2)</sup> rpm	Assembled inner ring LRT 455025											
D <sub>2</sub>	L	H			Radial	Radial			Axial										
71.5	35	25	14	10	0.6	0.3	50	67	49	42	200	43	300	83	400	148	000	5	000

Notes:  
(1) Minimum allowable value of chamfer dimension r.  
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NBX series.  
Remark:  
Z: The outer ring has an oil groove and an oil hole.  
2: Grease is not prepacked. Perform proper lubrication.

### CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952391021
Diametro interno	45 mm
Diametro esterno	62 mm
Spessore	35 mm
Imballaggio	1

[contatto@123cuscinetti.it](mailto:contatto@123cuscinetti.it)

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE