

## Cuscinetti a rullini NAXI5040-IKO - NAXI5040-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/rullini/naxi5040-iko>

**IICO**  
**COMBINED TYPE NEEDLE ROLLER BEARINGS**

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**  
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**

Identification number										
Shaft dia. mm	Mass (Ref.) g	With dust cover	Mass (Ref.) g	Mass (Ref.) g	With dust cover	Mass (Ref.) g	d	D	D <sub>1</sub>	
50	NAXI 5040	582	—	—	—	—	50	72	85	
Boundary dimensions mm										
D <sub>2</sub>	L	B	H	I <sub>1</sub>	r <sup>(1)</sup>	r <sup>(2)</sup>	d <sub>4</sub>	d <sub>5</sub>	Assembled inner ring	
86.5	40	25.5	17	12	1	1	60	75	LRT 506025	
Load ratings										
Basic dynamic load rating C		Basic static load rating C <sub>0</sub>		Allowable rotational speed <sup>(3)</sup>		Remarks				
Radial	Axial	Radial	Axial	Radial	Axial	rpm				
N	N	N	N	N	N					
47 500	41 400	103 000	89 700	4 000						

Notes:  
(1) Minimum allowable value of chamfer dimension r.  
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.  
Remark 1: The outer ring has an oil groove and an oil hole.  
2: Grease is not prepacked. Perform proper lubrication.

### CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952391045
Diametro interno	50 mm
Diametro esterno	72 mm
Spessore	40 mm
Imballaggio	1

[contatto@123cuscinetti.it](mailto:contatto@123cuscinetti.it)

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE