

Cuscinetti a rullini NAXI6040-IKO - NAXI6040-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/rullini/naxi6040-iko>

IKO
COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**

Identification number											
Shaft dia. mm	Mass (Ref.) g	With dust cover	Mass (Ref.) g	Mass (Ref.) g	With dust cover	Mass (Ref.) g	d	D	D ₁		
60	NAXI 6040	750	---	---	---	---	60	85	95		
Boundary dimensions mm											
D ₂	L	B	H	I ₁	r ⁽¹⁾	r _{max}	r _{min}	d ₄	d ₅	Radial	Axial
96.5	40	25.5	18	11	1	1	70	70	85	68	55
Basic dynamic load rating C											
Basic static load rating C ₀											
Allowable rotational speed ⁽²⁾											
										3 500	LRT 607025

Notes⁽¹⁾ Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. Grease is not prepacked. Perform proper lubrication.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952391083
Diametro interno	60 mm
Diametro interno	2.362" inch
Diametro esterno	85 mm
Diametro esterno	3.346" inch
Spessore	40 mm
Spessore	1.575" inch
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE