


## Snodi sferici GE GE140ES-IKO - GE140ES-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/ge/ge140es-iko>

**IKO**  
**SPHERICAL BUSHINGS**  
Steel-on-steel Spherical Bushings



Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						Permissible tilting angle degree		
	Without seals	With seals		d	D	B	C	d <sub>s</sub>	r <sub>1</sub> <sup>(1)</sup>	r <sub>2</sub> <sup>(1)</sup>	α	α <sub>1</sub>
140	<b>GE 140ES</b>		11.4	140	210	90	70	180	1	1	7	5
Mounting dimensions mm		Dynamic load capacity C <sub>d</sub>		Static load capacity C <sub>s</sub>								
d <sub>s</sub>		D <sub>s</sub>		N		N						
Min. Max. <sup>(2)</sup>		Min. Max.		N		N						
145.5 155.5		204.5 176		1 240 000		7 410 000						

Notes<sup>(1)</sup> Minimum allowable value of chamfer dimensions r<sub>1</sub> and r<sub>2</sub>.  
<sup>(2)</sup> When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d<sub>s</sub>.  
Remark: 1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.  
2. Not provided with prepacked grease. Perform proper lubrication for use.

## CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952392004
Diametro interno	140 mm
Diametro interno	5.512" inch
Diametro esterno	210 mm
Diametro esterno	8.268" inch
Spessore	90 mm
Spessore	3.543" inch
Tipo	GE
Peso	11265 g
Lubrificazione	senza
Imballaggio	1

[contatto@123cuscinetti.it](mailto:contatto@123cuscinetti.it)

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE