


Snodi sferici GE GE200ES-2RS-IKO - GE200ES-2RS-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/ge/ge200es-2rs-iko>

IKO
SPHERICAL BUSHINGS
Steel-on-steel Spherical Bushings



Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						Permissible tilting angle degree		
	Without seals	With seals		d_a	D	B	C	d_s	r_1 (1)	r_2 (1)	α	α_1
200	GE 200ES-2RS		26.1	200	290	130	100	250	1.1	1.1	7	6
Mounting dimensions mm		Dynamic load capacity C_d		Static load capacity C_s								
d_a	D_s	C_d	C_s									
Min. Max.(2)	Max. Min.	N	N									
207 213.5	283 244	2 450 000	14 700 000									

Notes (1) Minimum allowable value of chamfer dimensions r_1 and r_2 .
(2) When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_a .
Remark: The inner ring and the outer ring have an oil groove and two oil holes, respectively.
2. Not provided with prepacked grease. Perform proper lubrication for use.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952392066
Diametro interno	200 mm
Diametro interno	7.874" inch
Diametro esterno	290 mm
Diametro esterno	11.417" inch
Spessore	130 mm
Spessore	5.118" inch
Tipo	GE
Lubrificazione	senza
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE