

Snodi sferici GE GE220ES-IKO - GE220ES-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/ge/ge220es-iko>

SPHERICAL BUSHINGS
steel Spherical Bushings

| Identification number | | Mass (Ref.) kg | Boundary dimensions mm | | | | | | Per mitt ε |
|-----------------------|------------|-------------------|---------------------------|------------|------------|------------|------------|------------------------------------|------------------|
| Without seals | With seals | | d | D | B | C | dk | r _{1s} min ⁽¹⁾ | |
| GE 220ES | | 36.1 | 220 | 320 | 135 | 100 | 275 | 1.1 | 1.1 |

| Mounting dimensions mm | | | Dynamic load capacity C _D N | Static load capacity C _S N |
|---------------------------|------|------|---|--|
| Max. ⁽²⁾ | Max. | Min. | | |
| 239.5 | 313 | 269 | 2 700 000 | 16 200 000 |

Minimum allowable value of chamfer dimensions r₁ and r₂
When Spherical Bushings are used with full filling angle, the shaft shoulder dimension must be less than the maximum value.
The inner ring and the outer ring have an oil groove and two oil holes, respectively.
Not provided with prepacked grease. Perform proper lubrication for use.

CARATTERISTICHE DEL PRODOTTO

| | |
|------------------|---------------|
| Marchio | IKO |
| N° Ean13 | 3663952392080 |
| Diametro interno | 220 mm |
| Diametro esterno | 320 mm |
| Spessore | 135 mm |
| Tipo | GE |
| Lubrificazione | senza |
| Imballaggio | 1 |

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE