

## Snodi sferici GE GE220ES-2RS-IKO - GE220ES-2RS-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/ge/ge220es-2rs-iko>

**IKO**  
**SPHERICAL BUSHINGS**  
Steel-on-steel Spherical Bushings



Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						Permissible tilting angle degree			
	Without seals	With seals		$d$	$D$	$B$	$C$	$d_s$	$r_1$ (1)	$r_2$ (1)	$\alpha$	$\alpha_1$	
<b>220</b>		<b>GE 220ES-2RS</b>	36,1	220	320	135	100	275	1,1	1,1	8	6	
Mounting dimensions mm		Dynamic load capacity $C_d$ N	Static load capacity $C_s$ N	$d_s$		$D_s$							
Min.	Max. (2)			Min.	Max.	Min.	Max.	Min.	Max.				
227	239,5	313	269	2 700 000	16 200 000								

Notes (1) Minimum allowable value of chamfer dimensions  $r_1$  and  $r_2$ .  
(2) When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of  $d_s$ .  
Remark: 1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.  
2. Not provided with prepacked grease. Perform proper lubrication for use.

## CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952392097
Diametro interno	220 mm
Diametro esterno	320 mm
Spessore	135 mm
Tipo	GE
Lubrificazione	senza
Imballaggio	1

[contatto@123cuscinetti.it](mailto:contatto@123cuscinetti.it)

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE