


Snodi sferici GE GE240ES-IKO - GE240ES-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/ge/ge240es-iko>

IKO
SPHERICAL BUSHINGS
Steel-on-steel Spherical Bushings



Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						Permissible tilting angle degree		
	Without seals	With seals		d_1	D	B	C	d_s	r_1 (1)	r_2 (1)	α	α_1
240	GE 240ES		40,4	240	340	140	100	300	1,1	1,1	8	6
Mounting dimensions mm			Dynamic load capacity C_d N	Static load capacity C_s N								
d_s	D_s				Min.	Max. (2)	Min.	Max.	Min.	Max.	Min.	Max.
247	265	333	2 940 000	17 700 000								

Notes (1) Minimum allowable value of chamfer dimensions r_1 and r_2 .
(2) When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_s .
Remark: The inner ring and the outer ring have an oil groove and two oil holes, respectively.
2. Not provided with prepacked grease. Perform proper lubrication for use.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952392110
Diametro interno	240 mm
Diametro esterno	340 mm
Spessore	140 mm
Tipo	GE
Lubrificazione	senza
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE