


Snodi sferici GE GE260ES-IKO - GE260ES-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/ge/ge260es-iko>

IKO
SPHERICAL BUSHINGS
Steel-on-steel Spherical Bushings



Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						Permissible tilting angle degree		
	Without seals	With seals		d	D	B	C	d _s	r ₁ ⁽¹⁾ mm	r ₂ ⁽¹⁾ mm	α	α ₁
260	GE 260ES		52.0	260	370	150	110	325	1.1	1.1	7	6
Mounting dimensions mm		Dynamic load capacity C _d		Static load capacity C _s								
d _s		D _s		N								
Min.	Max. ⁽²⁾	Min.	Max.	Min.	Max.							
267	288	363	320	3 510 000	21 000 000							

Notes⁽¹⁾ Minimum allowable value of chamfer dimensions r₁ and r₂.
⁽²⁾ When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_s.
Remark: 1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.
2. Not provided with prepacked grease. Perform proper lubrication for use.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952392127
Diametro interno	260 mm
Diametro esterno	370 mm
Spessore	150 mm
Tipo	GE
Lubrificazione	senza
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE