Snodi sferici GE
GE90GS-IKO - GE90GS-IKO

https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/ge/ge90gs-iko



IKO

SPHERICAL BUSHINGS

Steel-on-steel Spherical Bushings

GE···GS

Shaft dia.	Identification number		Mass (Ref.)	Boundary dimensions mm							Permissible tilting angle degree	
mm	Without seals	With seals	kg	d	D	B	C	d_k	$r_{1s\ min}$ (1)	$r_{2s\ min}$ (1)	α	α_1
90	GE 90GS		5.41	90	150	85	55	130	1	1	15	14

Mounting dimensions mm				Dynamic load capacity C_d	Static load capacity C_s
d_a		D_a			
Min.	Max.(2)	Max.	Min.	N	N
95.5	98	144.5	127	701 000	4 210 000

Notes(1) Minimum allowable value of chamfer dimensions r_1 and r_2.
(2) When Spherical Bushings are used with full tilting angle, the shaft shoulder dimesion must be less than the maximum value of d_a.
Remarks1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.
2. Not provided with prepacked grease. Perform proper lubrication for use.

123BEARING

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952392479
Diametro interno	90 mm
Diametro esterno	150 mm
Spessore	85 mm
Tipo	GE
Lubrificazione	senza
Imballaggio	1

contatto@123cuscinetti.it
+33 3 59 36 04 90
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE