


Snodi sferici GE GE100GS-2RS-IKO - GE100GS-2RS-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/ge/ge100gs-2rs-iko>

IKO
SPHERICAL BUSHINGS
Steel-on-steel Spherical Bushings



Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						Permissible tilting angle degree			
	Without seals	With seals		d	D	B	C	d _s	r ₁ ⁽¹⁾ min	r ₂ ⁽¹⁾ min	α	α ₁	
100		GE 100GS-2RS	6.15	100	160	85	55	140	1	1	14	12	
Mounting dimensions mm		Dynamic load capacity C _d		Static load capacity C _s									
d _s		D _s		N		N							
Min.	Max. ⁽²⁾	Max.	Min.	N		N							
105.5	111	154.5	138	755 000		4 530 000							

Notes⁽¹⁾ Minimum allowable value of chamfer dimensions r₁ and r₂.
⁽²⁾ When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_s.
Remark: 1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.
2. Not provided with prepacked grease. Perform proper lubrication for use.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952392493
Diametro interno	100 mm
Diametro interno	3.937" inch
Diametro esterno	160 mm
Diametro esterno	6.299" inch
Spessore	85 mm
Spessore	3.346" inch
Tipo	GE
Lubrificazione	senza
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE