

## Snodi sferici GE GE220GS-2RS-IKO - GE220GS-2RS-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/ge/ge220gs-2rs-iko>

**IKO**  
**SPHERICAL BUSHINGS**  
Steel-on-steel Spherical Bushings



Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						Permissible tilting angle degree		
	Without seals	With seals		D	D	B	C	d <sub>s</sub>	r <sub>1</sub> <sup>(1)</sup> mm	r <sub>2</sub> <sup>(1)</sup> mm	α	α <sub>1</sub>
220		GE 220GS-2RS	51.3	220	340	175	100	300	1.1	1.1	16	14
Mounting dimensions mm		Dynamic load capacity C <sub>d</sub>		Static load capacity C <sub>s</sub>								
d <sub>s</sub>	D <sub>s</sub>	C <sub>d</sub>	C <sub>s</sub>									
Min.	Max. <sup>(2)</sup>	Min.	N									
227	243.5	333	296	2 940 000	17 700 000							

Notes<sup>(1)</sup> Minimum allowable value of chamfer dimensions r<sub>1</sub> and r<sub>2</sub>.  
<sup>(2)</sup> When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d<sub>s</sub>.  
 Remark: 1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.  
 2. Not provided with prepacked grease. Perform proper lubrication for use.

### CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952392646
Diametro interno	220 mm
Diametro esterno	340 mm
Spessore	175 mm
Tipo	GE
Lubrificazione	senza
Imballaggio	1

[contatto@123cuscinetti.it](mailto:contatto@123cuscinetti.it)

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE