


Snodi sferici GE GE260GS-IKO - GE260GS-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/ge/ge260gs-iko>

IKO
SPHERICAL BUSHINGS
Steel-on-steel Spherical Bushings



Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						Permissible tilting angle degree		
	Without seals	With seals		D	D	B	C	d _s	r ₁ ⁽¹⁾	r ₂ ⁽¹⁾	α	α ₁
260	GE 260GS		81.8	260	400	205	120	350	1.1	1.1	15	14
Mounting dimensions mm			Dynamic load capacity C _d N	Static load capacity C _s N								
d _s		D _s										
Min.	Max. ⁽²⁾	Max.	Min.									
267	283.5	393	345	4 120 000		24 700 000						

Notes⁽¹⁾ Minimum allowable value of chamfer dimensions r₁ and r₂.
⁽²⁾ When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_s.
Remark: 1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.
2. Not provided with prepacked grease. Perform proper lubrication for use.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952392677
Diametro interno	260 mm
Diametro esterno	400 mm
Spessore	205 mm
Tipo	GE
Lubrificazione	senza
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE