


Rullo di Scorrimento CRY36-VR-IKO - CRY36-VR-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rulli/rullo-scorrimento/cry36-vr-iko>

IKO
ROLLER FOLLOWERS
Non-separable Roller Followers, Inch Series **Full Complement Type / With Inner Ring**



| Shaft dia. mm (inch) | Identification number | | Mass (Ref.) g | Boundary dimensions: mm(inch) | | | | | |
|------------------------------------|---------------------------------------|---------------------------------------|---------------------|-------------------------------|---------------------------|--|---|-----------|--------|
| | Shield type Cylindrical outer ring | Sealed type Cylindrical outer ring | | d | D | B | C | | |
| 15.875 ($\frac{5}{8}$) | CRY 36 VR | | 599 | 15.875 ($\frac{5}{8}$) | 57.150 ($2\frac{1}{4}$) | 33.338 (1.3125) | 31.750 ($1\frac{1}{4}$) | | |
| d | f | Shaft dia. | | | | Basic dynamic load rating C N | Basic static load rating C_0 N | | |
| | | Push fit | | Drive fit | | | | Press fit | |
| | | Min. | Max. | Min. | Max. | Min. | Max. | | |
| 38.0 (1.417) | 600 ($\frac{24}{1}$) | 15.857 | 15.867 | 15.873 | 15.883 | 15.883 | 15.893 | 45 700 | 80 600 |

Remarks: 1. The inner ring has an oil hole.
2. Provided with prepacked grease.

CARATTERISTICHE DEL PRODOTTO

| | |
|------------------|---------------|
| Marchio | IKO |
| N° Ean13 | 3663952398938 |
| Diametro interno | 15.875 mm |
| Diametro esterno | 57.15 mm |
| Spessore | 33.338 mm |
| Imballaggio | 1 |

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE