


## Rotelle con perno CF10-1-VM-IKO - CF10-1-VM-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-sfera/rotelle-perno/cf10-1-vm-iko>



### CAM FOLLOWERS

Standard Type Cam Followers Full Complement Type/With Screwdriver Slot



| Stud dia.<br>mm        | Identification number   |                  |                             |                |                         |                |                             |                | CF-V                           |                           |   |   |  |       |
|------------------------|-------------------------|------------------|-----------------------------|----------------|-------------------------|----------------|-----------------------------|----------------|--------------------------------|---------------------------|---|---|--|-------|
|                        | Shield type             |                  |                             |                | Sealed type             |                |                             |                | Mass (Ref.)                    |                           | D   | C   | d <sub>1</sub>                           |       |
|                        | With crowned outer ring |                  | With cylindrical outer ring |                | With crowned outer ring |                | With cylindrical outer ring |                | g                              |                           |   |   |  |       |
| 10                     | CF 10-1 VM              |                  |                             |                |                         |                |                             |                | 61                             | 26                        | 12  | 10  |  |       |
| Boundary dimensions mm |                         |                  |                             |                |                         |                |                             |                |                                |                           |   |   |  |       |
| G                      | G <sub>1</sub>          | B <sub>max</sub> | B <sub>1 max</sub>          | B <sub>2</sub> | B <sub>3</sub>          | C <sub>1</sub> | g <sub>1</sub>              | g <sub>2</sub> | f <sup>(1)</sup><br>Min.<br>mm | Mounting<br>torque<br>N·m | Basic<br>dynamic<br>load rating<br>C<br>N | Basic<br>static<br>load rating<br>C <sub>0</sub><br>N | Maximum<br>allowable<br>static load<br>N |       |
| M10×1                  | 12                      | 13.2             | 36.2                        | 23             | —                       | 0.6            | *4                          | —              | 0.3                            | 16                        | 14.7                                      | 9 570   | 14 500                                   | 8 650 |

## CARATTERISTICHE DEL PRODOTTO

|                  |               |
|------------------|---------------|
| Marchio          | IKO           |
| N° Ean13         | 3663952440347 |
| Diametro interno | 10 mm         |
| Diametro esterno | 26 mm         |
| Spessore         | 12 mm         |
| Imballaggio      | 1             |

[contatto@123cuscinetti.it](mailto:contatto@123cuscinetti.it)

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE