


## Rotelle con perno CF12-V-IKO - CF12-V-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-sfera/rotelle-perno/cf12-v-iko>



### CAM FOLLOWERS

Standard Type Cam Followers Full Complement Type/With Screwdriver Slot



| Stud dia.<br>mm        | Identification number   |                  |                             |                |                         |                |                             |                | CF-V                           |                                       |                                |  |                               |        |
|------------------------|-------------------------|------------------|-----------------------------|----------------|-------------------------|----------------|-----------------------------|----------------|--------------------------------|---------------------------------------|--------------------------------|--|-------------------------------|--------|
|                        | Shield type             |                  |                             |                | Sealed type             |                |                             |                | Mass (Ref.)                    |                                       | D                              | C  | d <sub>1</sub>                |        |
|                        | With crowned outer ring |                  | With cylindrical outer ring |                | With crowned outer ring |                | With cylindrical outer ring |                | g                              | 30                                    | 14                             | 12   |                               |        |
| 12                     | CF 12 V                 |                  |                             |                |                         |                |                             |                |                                |                                       |                                |  |                               |        |
| Boundary dimensions mm |                         |                  |                             |                |                         |                |                             |                |                                |                                       |                                |  |                               |        |
| G                      | G <sub>1</sub>          | B <sub>max</sub> | B <sub>1 max</sub>          | B <sub>2</sub> | B <sub>3</sub>          | C <sub>1</sub> | g <sub>1</sub>              | g <sub>2</sub> | f <sup>(1)</sup><br>Min.<br>mm | Mounting diameter<br>f <sub>min</sub> | Maximum tightening torque<br>C | Basic static load rating<br>C <sub>0</sub> | Maximum allowable static load |        |
| M12×1.5                | 13                      | 15.2             | 40.2                        | 25             | 6                       | 0.6            | 6                           | 3              | 0.6                            | 21                                    | 21.9                           | 13 500                                     | 19 700                        | 13 200 |

## CARATTERISTICHE DEL PRODOTTO

|                  |               |
|------------------|---------------|
| Marchio          | IKO           |
| N° Ean13         | 3663952440408 |
| Diametro interno | 12 mm         |
| Diametro interno | 0.472" inch   |
| Diametro esterno | 30 mm         |
| Diametro esterno | 1.181" inch   |
| Spessore         | 14 mm         |
| Spessore         | 0.551" inch   |
| Imballaggio      | 1             |

[contatto@123cuscinetti.it](mailto:contatto@123cuscinetti.it)

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE