

## Rotelle con perno CFE30-1-VB-IKO - CFE30-1-VB-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-sfera/rotelle-perno/cfe30-1-vb-iko>

IKO

### CAM FOLLOWERS

Eccentric Type Cam Followers Full Complement Type/With Hexagon Hole



| Outside diameter of eccentric roller mm | Identification number   |                             |                         |                             |  |  | Mass (Ref.) |    |    |                |
|---|-------------------------|-----------------------------|-------------------------|-----------------------------|--|--|-------------|----|----|----------------|
|   | Shield type             |                             |                         | Sealed type                 |  |  | Ø           | D  | C  | d <sub>e</sub> |
|   | With crowned outer ring | With cylindrical outer ring | With crowned outer ring | With cylindrical outer ring |  |  |             |    |    |                |
| 41                                      | CFE 30-1 VB             |                             |                         |                             |  |  | 2 190       | 85 | 35 | 41             |

  

| Boundary dimensions mm |                |                       |                       |                |                |   |                         |                   |                                       |                                |                                     |   |                                    |         |        |
|------------------------|----------------|-----------------------|-----------------------|----------------|----------------|---|-------------------------|-------------------|---------------------------------------|--------------------------------|-------------------------------------|---|------------------------------------|---------|--------|
| G                      | B <sub>3</sub> | B <sub>1</sub><br>max | B <sub>2</sub><br>max | C <sub>1</sub> | G <sub>1</sub> | H | H <sub>max</sub><br>(1) | Eccentricity<br>g | Mounting dimension<br>f<br>Min.<br>mm | Maximum splining torque<br>N·m | Basic dynamic load rating<br>C<br>N | Basic static load rating<br>C <sub>0</sub><br>N | Maximum allowable static load<br>N |         |        |
| M30×1.5                | 32.5           | 37                    | 100                   | 63             | 1              | 8 | 30.5                    | 17                | 1                                     | 1.5                            | 49                                  | 438   | 67 700                             | 144 000 | 85 900 |

## CARATTERISTICHE DEL PRODOTTO

|                  |               |
|------------------|---------------|
| Marchio          | IKO           |
| N° Ean13         | 3616060460813 |
| Diametro interno | 41 mm         |
| Diametro interno | 1.614" inch   |
| Diametro esterno | 85 mm         |
| Diametro esterno | 3.346" inch   |
| Spessore         | 35 mm         |
| Spessore         | 1.378" inch   |
| Peso             | 2190 g        |
| Imballaggio      | 1             |

[contatto@123cuscinetti.it](mailto:contatto@123cuscinetti.it)

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE