

Rotelle con perno CFE12-1-V-IKO - CFE12-1-V-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-sfera/rotelle-perno/cfe12-1-v-iko>

IKO

CAM FOLLOWERS

Eccentric Type Cam Followers Full Complement Type/With Screwdriver Slot



| Outside diameter of eccentric roller mm | Identification number | | | | Mass (Ref.) | | | |
|--|-------------------------|-----------------------------|-------------------------|-----------------------------|-------------|----|----|----------------|
| | Shield type | | Sealed type | | g | D | C | d _e |
| | With crowned outer ring | With cylindrical outer ring | With crowned outer ring | With cylindrical outer ring | | | | |
| 16 | CFE 12-1 V | | | | 117 | 32 | 14 | 16 |

| Boundary dimensions mm | | | | | | | | | | | | | | |
|------------------------|----------------|------------------|-----------------------|----------------|----------------|----------------|----------------|-----------------------|-------------------|--|---------------------------------------|--|--|--|
| G | B ₃ | B _{max} | B ₁ max | B ₂ | C ₁ | g ₁ | G ₁ | r ₁ min | Eccentricity E | Mounting dimension f Min. mm | Maximum operating torque N·m | Basic dynamic load rating C N | Basic static load rating C ₀ N | Maximum allowable static load N |
| M12 × 1.5 | 11.5 | 15.2 | 40.2 | 25 | 0.6 | 6 | 13.5 | 0.6 | 0.8 | 21 | 21.9 | 13 500 | 19 700 | 13 200 |

CARATTERISTICHE DEL PRODOTTO

| | |
|------------------|---------------|
| Marchio | IKO |
| N° Ean13 | 3616060461063 |
| Diametro interno | 16 mm |
| Diametro esterno | 32 mm |
| Spessore | 14 mm |
| Peso | 117 g |
| Imballaggio | 1 |

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE