

Rotelle con perno CR30-B-IKO - CR30-B-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-sfera/rotelle-perno/cr30-b-iko>

IKO

CAM FOLLOWERS

Inch Series Cam Followers With Cage/With Hexagon Hole



| Stud dia. mm (inch) | Identification number | | | | Mass (Ref.) | Boundary dimensions mm/inch | | | | | | |
|---------------------------|----------------------------|--------------------------------|----------------------------|--------------------------------|----------------|-----------------------------|-------------|--------------|--|---|--|--|
| | Shield type | | Sealed type | | | g | D | C | d ₁ | G UNF | G ₁ | |
| | With covered outer ring | With cylindrical outer ring | With covered outer ring | With cylindrical outer ring | | | | | | | | |
| 19.050 (3/4) | CR 30 B | | | | 410 | 47.625 (1 7/8) | 25.400 (1) | 19.050 (3/4) | 7/16 | 22.225 (7/8) | | |
| | B | B ₂ | B ₃ | C ₁ | E ₁ | E ₂ | H | r | Bearing dimension f Mm (mm/inch) | Maximum spinning torque C N·m | Basic dynamic load rating C N | Basic static load rating C ₀ N |
| | 25.8125 | 44.450 (1 3/4) | 11.112 (3/8) | 0.794 (1/8) | 4.792 (3/8) | 3.969 (3/8) | 7.938 (3/4) | 1.988 (3/8) | 32.543 (1 1/8) | 100 | 25 100 | 38 200 |

CARATTERISTICHE DEL PRODOTTO

| | |
|------------------|---------------|
| Marchio | IKO |
| N° Ean13 | 3616060462688 |
| Diametro interno | 19.05 mm |
| Diametro esterno | 47.625 mm |
| Spessore | 25.4 mm |
| Peso | 410 g |
| Imballaggio | 1 |

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE