


Rotelle con perno CR26-IKO - CR26-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-sfera/rotelle-perno/cr26-iko>

IKO

CAM FOLLOWERS

Inch Series Cam Followers With Cage/With Screwdriver Slot



Stud dia. mm (inch)	Identification number				Mass (Ref.) g	D	C	d ₁	G UNF	G ₁
	Shield type		Sealed type							
15.875 (5/8)	With covered outer ring	With cylindrical outer ring	With covered outer ring	With cylindrical outer ring	260	41.275 (1 1/2)	22.225 (7/8)	15.875 (5/8)	1/2 - 18	19.050 (3/4)
Boundary dimensions mm(inch)										
B max	B ₂	B ₃	C ₁	δ ₁	δ ₂	r	Bearing dimension f Min. mm(inch)	Maximum tightening torque C N·m	Basic dynamic load rating C ₀ N	Basic static load rating C ₀ N
23.8 (9/16)	38.100 (1 1/2)	9.525 (3/8)	0.794 (1/16)	4.762 (3/16)	3.969 (1/8)	1.588 (1/16)	26.199 (1 1/16)	55.7	10 800	24 300

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3616060463005
Diametro interno	15.875 mm
Diametro esterno	41.275 mm
Spessore	22.225 mm
Peso	260 g
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE