


## Rotelle con perno CR24-VBUUR-IKO - CR24-VBUUR-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-sfera/rotelle-perno/cr24-vbuur-iko>

IKO

### CAM FOLLOWERS

Inch Series Cam Followers **With Cage/With Screwdriver Slot**



CR24-VBUUR

Stud dia. mm (inch)	Identification number				Mass (Ref.) g	D	C	d <sub>1</sub>	G UNF	G <sub>1</sub>	
	Shield type With cover outer ring	Shield type With cylindrical outer ring	Shield type With cylindrical outer ring	Shield type With cylindrical outer ring							
15.875 ( $\frac{5}{8}$ )			CR 24	VBUUR	230	38.100 ( $\frac{1}{2}$ )	22.225 ( $\frac{7}{8}$ )	15.875 ( $\frac{5}{8}$ )	$\frac{1}{4}$ -18	19.050 ( $\frac{3}{4}$ )	
Boundary dimensions mm(inch)						Mounting dimension f Min. mm(inch)	Maximum tightening torque N-m	Basic dynamic load rating C N	Basic static load rating C <sub>0</sub> N		
B max	B <sub>2</sub>	B <sub>3</sub>	C <sub>1</sub>	g <sub>1</sub>	g <sub>2</sub>					H	r
23.8 (0.93)	38.100 ( $\frac{1}{2}$ )	9.525 ( $\frac{3}{8}$ )	0.794 ( $\frac{1}{16}$ )	4.762 ( $\frac{3}{16}$ )	3.969 ( $\frac{5}{32}$ )	7.938 ( $\frac{1}{2}$ )	1.588 ( $\frac{1}{16}$ )	26.195 ( $\frac{1}{2}$ )	55.7	29 200	40 100

## CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3616060463920
Diametro interno	15.875 mm
Diametro esterno	38.1 mm
Spessore	22.225 mm
Peso	230 g
Imballaggio	1

[contatto@123cuscinetti.it](mailto:contatto@123cuscinetti.it)

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE